

OSTA 751-2



CASE	<ul style="list-style-type: none"> Step Advanced 2007 Mini Tower Micro Atx, 2x Fan 12cm (1 front, 1 rear) 2x 5.25" External Units, 2x 3.5" External Units, 2x 3.5" External Units 2x Usb 2.0, 1x Mic, 1x Spk
POWER	<ul style="list-style-type: none"> 450W max
CPU	<ul style="list-style-type: none"> Intel® Pentium® E5300 2.60GHz, FSB 800MHz, 2MB L2 cache
MEMORY	<ul style="list-style-type: none"> 2GB DDR2 800MHz
HARD DISK	<ul style="list-style-type: none"> 3.5", 250Gb SATA II 7200 rpm
MOTHERBOARD	<ul style="list-style-type: none"> Gigabyte® GA-G31M-ES2L, Support for 1333/1066/800 MHz FSB
BIOS	<ul style="list-style-type: none"> Award Bios 2x8Mb, Support DualBios™
CHIPSET	<ul style="list-style-type: none"> North Bridge: Intel® G31 Express Chipset, South Bridge: Intel® ICH7 VIDEO : Integrated in the North Bridge
STORAGE	<ul style="list-style-type: none"> 4 x SATA 3Gb/s connectors supporting up to 4 SATA 3Gb/s devices 1 x IDE connector supporting ATA-100/66/33 and up to 2 IDE devices 1 x floppy disk drive connector supporting up to 1 floppy disk drive
MEMORY SLOTS	<ul style="list-style-type: none"> 2 Ddr2 DIMM slots, support up to 4GB, Dual channel memory architecture
AUDIO	<ul style="list-style-type: none"> Chipset integrated by Realtek® ALC888
LAN	<ul style="list-style-type: none"> Realtek 8111C Gigabit Ethernet controller , Supports 10/100/1000Mb/s
I/O INTERNAL CONNECTOR	<ul style="list-style-type: none"> 1 x 24-pin ATX main power connector, 1 x 4-pin ATX 12V power connector 1 x floppy disk drive connector, 1 x IDE connector, 4 x SATA 3Gb/s connectors 1 x CPU fan header, 1 x system fan header, 1 x front panel header 1 x front panel audio header, 1 x CD In connector, 1 x power LED header 1 x S/PDIF Out header, 2 x USB 2.0/1.1 headers, 1 x chassis intrusion header
EXPANSION SLOTS	<ul style="list-style-type: none"> 1 x PCI Express x16 slot 1x PCI Express x1 slots 2 x PCI slots
I/O PORTS AND CONNECTORS	<ul style="list-style-type: none"> 1 x PS/2 keyboard port, 1 x PS/2 mouse port, 1 x parallel port 1 x serial port, 1 x D-Sub port, 1 x RJ-45 port 4 x USB 2.0/1.1 ports 3 x audio jacks (Line In/Line Out/Microphone)
STORAGE PERIPHERAL	<ul style="list-style-type: none"> Dvd Rw/Ram +/- 24x Dual Layer Sata Black, Card Reader 7in1
PERIPHERAL	<ul style="list-style-type: none"> Optical mouse, Keyboard
WARRANTY	<ul style="list-style-type: none"> 24 months on center
SOFTWARE	<ul style="list-style-type: none"> Compatible with Windows 7/Vista (All version), Cd Driver